



DETAIL "A"
SCALE: 2:1

DETAIL "B"
SCALE: 2:1

1. ANY OPEN, MISWIRING, SHORT, INTERMITTENT WIRING ARE NOT PERMITTED.
2. INSULATION RESISTANCE : 50 OHMS / 250V DC MIN.
3. EMPTY PIN 1,3,8,9,11,12,13. AND PIN 4,5 HIGH THAN OTHERS 1.9MM.

PIN OUT

P1	P2	Description
3	6	CAN High (J-2284)
5	14	CAN Low (J-2284)
6	10	J1850 Bus -
7	2	J1850 Bus +
1	5	Signal Ground
2	4	Chassis Ground
4	7	ISO 9141-2 K Line
8	15	ISO 9141-2 L Line
9	16	Battery Power

ITEM	DESCRIPTION
6	Delphi pin.
5	Outer Molded : 45P PVC, Color : BLACK
4	SCREWS : 4.0*30.5MM (4-4 OUNC), MOLDED BLACK.
3	P2 conn: OBD-II Connectors, NYLON 66 UL94V-0. BLACK.
2	P1 conn: DB9PIN, Female, Solder type, Inside Black.
1	Cable: UL2464 24AWG(7/0.20TC)*2PAIRS+ 24AWG(7/0.20TC) *5C + Foil Shielding OD=6.2±0.1mm, Jacket color: Black.

X±	X°±	OBD2CABLES.COM					
.X±	.X°±						
.XX±	.XX°±	UNITS: mm	PART NO.: 143301	© Copyright 2008			
		<table border="1"> <tr> <td>SCALE</td> <td>SHEET</td> <td>REV.</td> </tr> </table>			SCALE	SHEET	REV.
		SCALE	SHEET	REV.			
Property of OBD2Cables.com, cannot be used or reproduced without permission.							