

Specifiche Tecniche Inverter Solare

INPUT(DC)	Recommended Max PV Power (Wp)	450 x 2			
	Max DC Open Circuit Voltage (Vdc)	60			
	Max DC Input Current (Adc)	14 x 2			
	MPPT Tracking Accuracy	>99.5%			
	MPPT Tracking Range (Vdc)	22-55			
	Isc PV (absolute maximum) (Adc)	18 x 2			
	Maximum Inverter Backfeed Current to the Array (Adc)	0			
OUTPUT (AC)	Peak AC Output Power (Wp)	550			
	Rated AC Output Power (Wp)	500			
	Nominal Power Grid Voltage (Vac)	240	208	230	
	Allowable Power Grid Voltage (Vac)	211-264*	183-229*	configurable*	
	Allowable Power Grid Frequency (Hz)	59.3 a 60.5*		configurable*	
	THD	<3% (at rated power)			
	Power Factor (cos phi, fixed)	>0.99 (at rated power)			
	Rated Output Current (Aac)	2.08	2.40	2.17	
	Current (inrush)(Peak and Duration)	24A, 15us			
	Nominal Frequency (Hz)	60		50	
	Maximum Output Fault Current (Aac)	4.4A peak			
	Maximum Output Overcurrent Protection (Aac)	10			
		Maximum Number of Units Per Branch (20A) (All NEC adjustment factors have been considered)	7	6	7
SYSTEM EFFICIENCY	Weighted Averaged Efficiency (CEC)	95.50%			
	Night Time Tare Loss (Wp)	0.11			
PROTECTION FUNCTIONS	Over/Under Voltage Protection	Yes			
	Over/Under Frequency Protection	Yes			
	Anti-Islanding Protection	Yes			
	Over Current Protection	Yes			
	Reverse DC Polarity Protection	Yes			
	Overload Protection	Yes			
	Protection Degree	NEMA-6 / IP-66 / IP-67			
	Ambient Temperature	-40°F to +149°F (-40°C to +65°C)			
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)			
	Display	LED LIGHT			
	Communications	Power Line			
	Dimension (W-H-D)	10.91"x5.20"x1.97"(277x132x50 mm)			
	Weight	6.4 lbs. (2.9 kg)			
	Environment Category	Indoor and outdoor			
	Wet Location	Suitable			
	Pollution Degree	PD 3			
	Overvoltage Category	II(PV), III (AC MAINS)			
		Product Safety Compliance	UL 1741 CSA C22.2 No. 107.1	IEC/EN 62109-1 IEC/EN 62109-2	
		Grid Code Compliance* (Refer to the label for the detailed grid code compliance)	IEEE 1547	VDE-AR-N 4105* VDE V 0126-1-1/A1 G83/2, CEI 021 AS 4777.2 & AS 4777.3,EN50438	

Distribuito da: **FUTURA GROUP SRL**

Via Adige, 11 - 21013 Gallarate (VA) Tel. 0331-799775 - Fax. 0331-778112

Web site: www.futurashop.it Info tecniche: supporto@futuragroupsrl.it